

HOSPIVAC® G - EVISA

Lubricated technology



- Modular central vacuum system
- Personalised units fitting any type of implantation and accessibility
- Lubricated rotary vane vacuum pumps EVISA.R type
- Dual power supply (from 2 pumps)
- Shock mounted
- Available regulation modes (see the set-up layout)
- Option FLEXO constant vacuum : regulation device allowing to use small capacity receivers
- Remote monitoring with CYCLIC 2020 or PROCOM 2 control boards
- HEPA bacterial filtration
- Delivery pot for condensate recuperation
- Fit to NF EN ISO 7396-1 standard
- Integrated network alarm with MILLENIUM, CYCLIC 2020 and PROCOM 2 devices
- Suction and exhaust hoses delivered with each pump



Characteristics

HOSPIVAC® G EVISA lubricated pumps	Nominal capacity m³.h⁻¹		Power kW		Noise level dB(A)
	50 Hz	60 Hz	50 Hz	60 Hz	
HOSPIVAC® G - E25.R	28	33	0,75	0,9	59
HOSPIVAC® G - E40.R	44	53	1,1	1,32	58
HOSPIVAC® G - E65.R	68	81	1,5	1,8	67
HOSPIVAC® G - E100.R	100	120	2,2	2,64	67
HOSPIVAC® G - E150.R	132	156	3	3	69
HOSPIVAC® G - E200.R	200	240	4	4,8	71
HOSPIVAC® G - E300.R	300	360	5,5	6,6	72
HOSPIVAC® G - E350.R	360	432	7,5	9	72
HOSPIVAC® G - E400.R	426	511	9	10,8	72
HOSPIVAC® G - E500.R	513	616	11	13,2	73
HOSPIVAC® G - E600.R	635	769	13	15,6	74

Available set-up

	HOSPIVAC® G
PROCOM 2 (PM2) from 1 to 6 pumps	■
CYCLIC 2020 (C2020) 2 or 3 pumps	■
MILLENIUM (MIL) 2 or 3 pumps	■
LG7 1 pump	■
Bacterial filtration (wall mounted)	■

■ Available



Range complying with
93/42/CEE directive



MODULAR vacuum plants


for medical applications




Dimensions (mm)

CONTROL BOARDS


For 4 to 6 motors




For 1 to 3 motors



LG7 device



REPORT STATUS device



EVISA.R vacuum pumps shock mounted, see pages 28 & 61

Bacterial filtrations, see page 62

Vacuum receivers, see page 68

Power supply

- 3-phase, 400V+N+E / 50Hz (standard)
- 3-phase, 380V+N+E / 60Hz
- Other tensions and frequencies on request

HOSPIVAC® G - EVISA

Lubricated technology



Plant references

HOSPIVAC® G - ON/OFF regulation			E25.R	E40.R	E65.R	E100.R	E150.R	E200.R	E300.R					
HOSPIVAC® G	3-ph, 400V 50 Hz		911818	911819	914472	914473	914474	914475	916672					
HOSPIVAC® G	1-ph, 230V 50 Hz		916087	916088	-	-	-	-	-					
HOSPIVAC® G	3-ph, 380V 60 Hz		911818	911819	925022	925023	-	925024	925025					
HOSPIVAC® G -FLEXO constant vacuum regulation			E25.R	E40.R	E65.R	E100.R	E150.R	E200.R	E300.R	E350.R	E400.R	E500.R	E600.R	
HOSPIVAC® G	3-ph, 400V 50 Hz		919182	919183	919184	919185	919186	919187	919188	917639	918284	917640	918285	
HOSPIVAC® G	1-ph, 230V 50 Hz		919193	919194	-	-	-	-	-	-	-	-	-	
HOSPIVAC® G	3-ph, 380V 60 Hz		919182	919183	925027	925028	-	925029	925030	-	925031	-	-	
			E25.R	E40.R	E65.R	E100.R	E150.R	E200.R	E300.R	E350.R	E400.R	E500.R	E600.R	
On/Off or FLEXO constant vacuum control regulation 400V + N + E	C2020	2 pumps	724859			724860			724867					
		3 pumps	724920			724848			724839					
		2 pumps	724861			724862			724868					
	PM2	3 pumps	724826			724849			724934		724840			
		4 pumps	724863			724865			724841		724932			
		5 pumps	724864			724866			724929	724929	724933			
		6 pumps	724827			724850			724930	724931	724870			
On/Off control regulation 400V+N+E	MIL	2 pumps	724857			724858			-					
		3 pumps	724921			724922			-					
FLEXO constant vacuum 400V+N+E	MIL	2 pumps	724924			724923			-					
		3 pumps	724825			724847			-					
ON/OFF regulation LG7 + vacuum gauge + switch (400V+N+E)			717743	717744		717745	717746	717747		-				
ON/OFF regulation LG7 + vacuum gauge + switch (1-ph 230V)			718296	718297	-									
Constant vacuum regulation LG7 + vacuum gauge + switch (400V+N+E)			719337	719338		719339	719340	719341		-				
Constant vacuum regulation LG7 + vacuum gauge + switch (1-ph 230V)			719342	719343	-									
			Filtration to be chosen according to the flow rate of the installation											
❶ Bacterial filtration delivered separately (wall mounting)	Single with by-pass		FD30B 811848		FD65B 811849		FD130B 811850		FD320B 811851		FD600B 811852		FD1000B 814915	
	Without by-pass + isolating valve		2 x FD1000S 2 x 817753											
	Parallel DUPLEX		FD60DP 814967		FD130DP 814968		FD260DP 814969		FD640DP 814970		FD1200DP 814971		FD2000DP 820146	

Specifications are subject to be changed without notice

MODULAR vacuum plants

for medical applications



Accessories and option references

		E25.R	E40.R	E65.R	E100.R	E150.R	E200.R	E300.R	E350.R	E400.R	E500.R	E600.R
Oil level security	PM2	625020 x X		625369 x X		624245 x X			623314 x X			
Oil level + T°C securities	PM2	724693 x X		724954 x X		624247 x X			623979 x X			
Oil level security	C2020/MIL	724694 x X		724955 x X		619196 x X			623332 x X			
Oil level + T°C securities	C2020/MIL	724695 x X		724956 x X		623325 x X			623326 x X			
Transformer 400V/230V		If no neutral available										611099
② Report Status (with electrical cords)	PM2	12 first alarms			625642		12 following alarms					625643
	C2020											625641
Back up power supply 24V	PM2	with battery										625004
FLEXO or ON/OFF external control		only with CYCLIC 2020 - weekly clock										613996
Clock forced running		only with CYCLIC 2020 - possible if FLEXO control										617608
Audio-warning system for MILLENIUM												618295
③ Lowest level drip pot		PR30			712068			PR60			706547	
Bacterial cartridge at exhaust		711103		717263		-						
	1 pump	617610		617611		617612			617613		624329	
Elevated base frame	2 pumps	619543		619544		619545			-			
	3 pumps	619546		617614		-						
④ Advised receiver for running with a FLEXO constant vacuum regulation device	2 pumps	500 l 710486		1000 l 710488		2000 l 722341					2 x 2000 l 2 x 722341	
	3 pumps	500 l 710486		1000 l 710488		2000 l 722341			2 x 2000 l 2 x 722341		3 x 2000 l 3 x 722341	
Vertical receiver for ON/OFF control regulation		Contact us										
⑤ Independent network connection alarm		1 vacuum switch and 1 vacuum gauge (dry contact)										708510

① Bacterial filtration



② Report status device



③ Lowest level drip pot



④ Vertical vacuum receiver



⑤ Network connection alarm

